# Technology Opportunity

# Two-Dimensional Analysis and Design Codes for Turbomachinery

The National Aeronautics and Space Administration (NASA) seeks to transfer NASA-developed two-dimensional (2-D) methods for analyzing and designing turbomachinery blading.

### **Potential Commercial Uses**


- Conceptual design of compressors
- Design of axial or centrifugal compressors
- Detailed performance maps for operation
- Development of commercial pump and compressor designs
- Aircraft propulsion
- · Auxiliary power
- · Automotive engines
- · Turbochargers

#### **Benefits**

- Higher efficiencies
- Faster design cycle times
- Lower direct operating costs
- · Improved reliability

## The Technology

Two-dimensional methods for analyzing and designing turbomachinery blading have been developed to determine the spanwise distributions of aerothermodynamic parameters. The codes typically can be used to determine stage loading, blade row turning, and efficiency potential. They can also be used to estimate the performance, pressure loads, and preliminary flow path and blading. The codes



Two-dimensional flow computation.

Blade sections for fan rotor.



were developed as a design/analysis method capable of determining the performance of a compressor with a higher degree of fidelity.

Over a 30-year time period NASA Lewis Research Center has conducted substantial compressor aerodynamic research, which served as a basis for the development of 2-D codes. These codes are robust, fairly fast computationally, and reasonably accurate. They require minimal input and are best used to analyze and compute the more detailed characteristics of compressor aerodynamics.

#### **Options for Commercialization**

NASA Lewis Research Center has no patents on the codes and release is subject to export law controls. Any company may acquire the codes and improve on the capability to create a preliminary compressor design. The codes may be used to develop and enhance design tools for commercial applications.

#### Contact

NASA Lewis Commercial Technology Office

NASA Lewis Research Center

Cleveland, OH 44135 Phone: (216) 433-5565 Fax: (216) 433-5012 E-mail: lbis@lerc.nasa.gov

David Salay, Manager of Client Services

Great Lakes Industrial Technology Center (GLITeC)

Phone: (216) 734-0094 Fax: (216) 734-0686 E-mail: salay@battelle.org

#### **Key Words**

Compressor performance Compressor 2-D analysis/design tools Computational fluid dynamics Grid generation

Compressor Research and Development 2-D Codes

(a) Description of NASA compressor aerothermodynamic prediction codes

(a) Description of the issue compressor acromormous name prediction codes					
Code	Brief Code Description				
CDP	Compressor design program; axial fan/compressors; geometry generation				
COD	Compressor off-design program				
CCGEOM	Geometry generation code				
TIGGERC	2-D interactive generic grid generator; operates on SGI platforms				
MTSB	Meridl, Tsonic Blayer coupled analysis package for turbomachinery				
DVC2D	Advanced 2-D axisymmetric viscous duct solver				
RVCQ3D	Quasi-3-D blade-to-blade viscous turbomachinery flow solver				
PCPANEL	Airfoil panel method solver				

(b) Aerothermodynamic code requirements and uses in various compressor design stages

Preliminary design	Code characteristics	Typical trade studies	Aerothermodynamic
stage			uses
•CDP	Robust; User	Spanwise distribution	Performance prediction;
•COD	friendly; Fast	of aerothermodynamic	Pressure loads;
<ul><li>PCPANEL</li></ul>	computationally; Good	parameters; Flow path	Conception of flow path
•CCGEOM	accuracy	definition; Grid	and blading
<ul> <li>MTSB/CCGEOM</li> </ul>		generation; Detailed	
•RVCQ3D		blading	
•TIGGERC (2D)			
•DVC2D			

(c) Experience and time requirements for NASA compressor aerothmodynamic prediction codes

Code	Typical user experience	Typical time required to	Set-up time	Typical times for an average	Computer required	Where to obtain the code
	emperionee	learn code		case	required	ine code
CDP	Moderate	~2 wk	< 2 days	~seconds	PC	COSMIC/Lewis
COD	Moderate	~2 wk	< 2 days	~seconds	PC	COSMIC/Lewis
CCODP	Low	~1 wk	~minutes	~seconds	PC	Lewis
CCGEOM	Low	~1 wk	~minutes	~seconds	PC	Lewis
TIGGERC	Moderate	~2 wk	<1 day	~seconds	Mini	COSMIC/Lewis
MTSB	Moderate	~2 wk	<1 wk	~seconds	PC/mini	COSMIC/Lewis
DVC2D	Moderate	~2 - 3 wk	<1 wk	~minutes	PC/mini	Lewis
PCPANEL	Low	~1 wk	~minutes	~seconds	PC/mini	Lewis

